

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
6030	Bell Cut-Off Timer - 6VDC or 12VDC, SPDT contacts rated @ 8 amp/115VAC.	\$11.47	19.78
6062	Multi-Function Timer - 12VDC or 24VDC operation, SPDT contacts rated @ 8 amp/115VAC, 1 sec. to 60 min. adjustable timing range. One second momentary relay activation at the end of timing cycle.	\$17.01	29.33
ACM4	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Listed sub-assembly.	\$37.38	64.44
ACM4CB	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, UL Listed sub-assembly.	\$37.38	64.44
ACM4CBE	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, encl. 8"H x 7.25"W x 3.5"D, UL Listed, cUL Listed.	\$64.44	111.11
ACM4E	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, encl. 8"H x 7.25"W x 3.5"D, UL Listed, cUL Listed.	\$64.44	111.11
ACM8	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Recognized Component.	\$48.98	84.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ACM8CB	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, UL Recognized Component.	\$48.98	84.44
ACM8CBE	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, encl. 13.5"H x 13"W x 3.25"D, UL Listed, cUL Listed.	\$76.04	131.11
ACM8E	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, encl. 13.5"H x 13"W x 3.25"D, UL Listed, cUL Listed.	\$76.04	131.11
AL1002ULADA	NAC Power Extender - 24VDC @ 10 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex & Potter sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL864), MEA, CSFM & FM Approved.	\$277.11	477.78
AL1002ULADAJ	NAC Power Extender - 24VDC @ 10 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex & Potter sync protocols, two - 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL864), MEA, CSFM Approved.	\$296.44	511.11
AL100UL	Power Supply/Charger - 12VDC @ 750mA, Class 2 power limited output, encl. 8.5"H x 7.5" W x 3.5"D, 16VAC 20VA Plug-in xfmr required, UL Listed (UL603).	\$59.55	102.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL1012ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$248.11	427.78
AL1012ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$248.11	427.78
AL1012ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$267.44	461.11
AL1012ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$267.44	461.11
AL1012ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	\$231.36	398.89
AL1012ULX	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$199.13	343.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL1012ULXB	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, non-power limited output, 115VAC input. UL Recognized.	\$147.58	254.44
AL1012ULXPD16	16 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$230.07	396.67
AL1012ULXPD16CB	16 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$230.07	396.67
AL1012ULXPD4	4 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$212.02	365.56
AL1012ULXPD4CB	4 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$212.02	365.56
AL1012ULXPD8	8 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$214.60	370.00
AL1012ULXPD8CB	8 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$214.60	370.00
AL1024ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$273.89	472.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL1024ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$273.89	472.22
AL1024ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$293.22	505.56
AL1024ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$293.22	505.56
AL1024ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	\$257.13	443.33
AL1024ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	\$257.13	443.33
AL1024ULX	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$224.91	387.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL1024ULXB2	Power Supply/Charger - 24VDC @ 10 Amp, AC & battery monitoring, non-power limited output, 115VAC input. UL Recognized.	\$173.36	298.89
AL1024ULXPD16	16 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$255.84	441.11
AL1024ULXPD16CB	16 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$255.84	441.11
AL1024ULXPD4	4 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$237.80	410.00
AL1024ULXPD4CB	4 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$237.80	410.00
AL1024ULXPD8	8 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$240.38	414.44
AL1024ULXPD8CB	8 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$240.38	414.44
AL1024ULXR	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, non-power limited output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$224.91	387.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL1042ULADA	NAC Power Extender - 24VDC @ 10 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex & Potter sync protocols, two - 1 amp aux. outputs, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL864) MEA, CSFM & FM Approved.	\$315.78	544.44
AL125UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$76.75	132.33
AL125ULB	Power Supply/Charger - 12VDC or 24VDC @ 1 amp, latching/non-latching fire alarm disconnect, (24VAC 40VA Plug-in xfmr required), UL Recognized.	\$36.09	62.22
AL125ULE	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 1 amp or 24VDC @ .5 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$58.39	100.67
AL125ULP	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 1 amp or 24VDC @ .5 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input (Includes TP2440 plug-in xfmr), UL Listed (UL294), cUL Listed.	\$75.40	130.00
AL125ULX	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1 amp, Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	\$85.07	146.67
AL168175CB	8 Output Control Panel Power Supply - 16VAC @ 10 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$126.31	217.78
AL168300CB	8 Output Control Panel Power Supply - 16VAC @ 18 amp or 18VAC @ 16 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$154.67	266.67
AL168300CBM	8 Output Control Panel Power Supply - 16VAC @ 18 amp or 18VAC @ 16 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input.	\$148.22	255.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL168600CB	8 Output Control Panel Power Supply - 16VAC @ 36 amp or 18VAC @ 32 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$167.56	288.89
AL168CB	8 Output Control Panel Power Supply - 16VAC @ 6 amp or 18VAC @ 5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$116.00	200.00
AL175UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1.75 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$96.67	166.67
AL175ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, latching/non-latching fire alarm disconnect, (28VAC 56VA xfmr required), UL Recognized.	\$54.13	93.33
AL175ULX	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1.75 amp, Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	\$109.56	188.89
AL175ULX2	2 Class 2 power limited outputs, 12VDC or 24VDC @ 1.75 amp, fire alarm disconnect, Reset switch, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$154.67	266.67
AL176UL	Power Supply/Charger - 12VDC or 24 VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, cULus Listed (UL294).	\$96.67	166.67
AL176ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, AC fail & low battery monitoring, (28VAC 56VA xfmr required), UL Recognized.	\$54.13	93.33
AL176ULX	Power Supply/Charger - 12VDC or 24 VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, cULus Listed (UL294).	\$109.56	188.89
AL201UL	Power Supply/Charger - 12VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 8.5"H x 7.5" W x 3.5"D, 115VAC input, UL Listed (UL294/UL603).	\$77.14	133.00
AL201ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, AC & battery monitoring, UL Recognized.	\$54.13	93.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL300ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	\$172.71	297.78
AL300ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	\$172.71	297.78
AL300ULPD4	4 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$153.38	264.44
AL300ULPD4CB	4 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$153.38	264.44
AL300ULPD8	8 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$155.96	268.89
AL300ULPD8CB	8 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$155.96	268.89
AL300ULX	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	\$140.49	242.22
AL300ULXB2	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, 115VAC input, UL Recognized.	\$102.47	176.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL300ULXD	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, encl. 15.5"H x 12"W x 4.5"D, 115/230VAC input, UL Listed (UL294/UL603/UL1069/UL1481), CSFM & MEA Approved.	\$154.02	265.56
AL300ULXPD16	16 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$171.42	295.56
AL300ULXPD16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$171.42	295.56
AL300ULXR	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	\$140.49	242.22
AL400UL	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, encl. 12.25"H x 7.5"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), CSFM & MEA Approved.	\$141.78	244.44
AL400UL3	Triple Voltage Power Supply/Charger - 5VDC & 12VDC @ 1.75 amp & 24VDC @ 1.5 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	\$227.49	392.22
AL400UL3X	Triple Voltage Power Supply/Charger - 5VDC & 12VDC @ 1.75 amp & 24VDC @ 1.5 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved..	\$240.38	414.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL400ULACM	Power Supply/Charger with Access power controller - 8 fused Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$197.20	340.00
AL400ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$197.20	340.00
AL400ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$216.53	373.33
AL400ULACMJ	Power Supply/Charger with Access power controller - 8 fused Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$216.53	373.33
AL400ULB	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, (28VAC 175VA xfmr required), UL Recognized.	\$92.03	158.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL400ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	\$180.44	311.11
AL400ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	\$180.44	311.11
AL400ULPD4	4 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$161.11	277.78
AL400ULPD4CB	4 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$161.11	277.78
AL400ULPD8	8 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$163.69	282.22
AL400ULPD8CB	8 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$163.69	282.22
AL400ULX	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$148.22	255.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL400ULXB2	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, 115VAC input, UL Recognized.	\$121.48	209.44
AL400ULXPD16	16 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$179.16	308.89
AL400ULXPD16CB	16 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	\$179.16	308.89
AL400ULXR	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$148.22	255.56
AL600UL3	Triple Voltage Power Supply/Charger - Class 2 power limited outputs 5VDC & 12VDC @ 1.75 amp & 24VDC @ 3 amp non power limited output, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	\$302.89	522.22
AL600UL3X	Triple Voltage Power Supply/Charger - Class 2 power limited outputs 5VDC & 12VDC @ 1.75 amp & 24VDC @ 3 amp non power limited output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	\$315.78	544.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL600ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$248.11	427.78
AL600ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	\$248.11	427.78
AL600ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$267.44	461.11
AL600ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	\$267.44	461.11
AL600ULB	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, (Two 28VAC 100VA xfmr required), UL Recognized.	\$109.56	188.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL600ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, MEA & CSFM Approved.	\$231.36	398.89
AL600ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, MEA & CSFM Approved.	\$231.36	398.89
AL600ULPD4	4 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$212.02	365.56
AL600ULPD4CB	4 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$212.02	365.56
AL600ULPD8	8 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$214.60	370.00
AL600ULPD8CB	8 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$214.60	370.00
AL600ULX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$199.13	343.33
AL600ULXB	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, 115VAC input, UL Recognized.	\$147.58	254.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL600ULXD	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115/230VAC input, UL Listed (UL294/UL1481).	\$206.22	355.56
AL600ULXPD16	16 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$230.07	396.67
AL600ULXPD16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	\$230.07	396.67
AL600ULXR	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	\$199.13	343.33
AL602ULADA	NAC Power Extender - 24VDC @ 6.5 amp, 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex & Potter sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM & FM Approved.	\$225.56	388.89
AL602ULADAJ	NAC Power Extender - 24VDC @ 6.5 amp, 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex & Potter sync protocols, 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM Approved.	\$244.89	422.22
AL624	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA.	\$10.72	18.49
AL62412C	Linear Power Supply/Charger - 12VDC @ 1.2 amp, 12VDC/4AH battery & 16.5VAC/20VA plug-in xfmr.	\$43.44	74.90
AL62412CX	Linear Power Supply/Charger - 12VDC @ 1.2 amp, 12VDC/7AH battery & 16.5VAC/20VA plug-in xfmr.	\$47.44	81.80
AL62424C	Linear Power Supply/Charger - 24VDC @ 750mA, two 12VDC/4AH batteries & 24VAC/40VA plug-in xfmr.	\$68.06	117.35

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AL624E	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, encl. 8.5"H x 7.5"W x 3.5"D.	\$32.87	56.67
AL624ET	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, 16VAC/20VA plug-in xfmr, encl. 8.5"H x 7.5"W x 3.5"D.	\$39.63	68.33
AL642ULADA	NAC Power Extender - 24VDC @ 6.5 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex & Potter sync protocols, two - 1 amp aux. outputs, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481) MEA, CSFM & FM Approved.	\$264.22	455.56
AL802ULADA	NAC Power Extender - 24VDC @ 8 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex & Potter sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM & FM Approved.	\$268.09	462.22
AL802ULADAJ	NAC Power Extender - 24VDC @ 8 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex & Potter sync protocols, 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM Approved.	\$287.42	495.56
AL842ULADA	NAC Power Extender - 24VDC @ 8 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes. Generates System Sensor, Gentex & Potter sync protocols, two - 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481) MEA, CSFM & FM Approved.	\$306.76	528.89
ALSD1	2 Channel Siren Driver - 6VDC to 12VDC operation, Yelp & Steady, High output, Current draw 0.5 to 1.8 amp is based on speaker resistance & input voltage.	\$11.99	20.67
ALSD2	2 Channel Siren Driver - 6VDC to 12VDC operation, Yelp & Steady, Current draw 0.3 to 1.22 amp is based on speaker resistance & input voltage.	\$8.64	14.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV1224C	16 Output CCTV Power Supply - eight 24VAC @ 3.5 amp plus eight 12VDC @ 3.5 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$150.80	260.00
ALTV1224C4	4 Output CCTV Power Supply - two 24VAC @ 4 amp plus two 12VDC @ 4 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$132.76	228.90
ALTV1224DC	8 Output CCTV Power Supply - 12VDC or 24VDC @ 4 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$122.44	211.10
ALTV1224DC1	16 Output CCTV Power Supply - 12VDC or 24VDC @ 4 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$134.04	231.11
ALTV1224DC2	16 Output CCTV Power Supply - 12VDC or 24VDC @ 6 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$141.78	244.44
ALTV2416	16 Output CCTV Power Supply - 24VAC @ 8 amp or 28VAC @ 7 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$106.68	183.93
ALTV2416300UCBM	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416300UCM3 - Includes factory installed 3-wire line cord.	\$134.69	232.22
ALTV2416300UL	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416300UL3 - Includes factory installed 3-wire line cord.	\$141.13	243.33
ALTV2416300ULCB	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416300UCB3 - Includes factory installed 3-wire line cord.	\$141.13	243.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV2416300ULM	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416300ULM3 - Includes factory installed 3-wire line cord.	\$134.69	232.22
ALTV2416350	16 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$141.13	243.33
ALTV2416350CB	16 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$141.13	243.33
ALTV2416600	16 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$194.11	334.67
ALTV2416600CB	16 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$194.11	334.68
ALTV2416600UL	16 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416600UL3 - Includes factory installed 3-wire line cord.	\$194.11	334.67
ALTV2416600ULCB	16 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416600UCB3 - Includes factory installed 3-wire line cord.	\$194.11	334.67
ALTV2416CB	16 Output CCTV Power Supply - 24VAC @ 8 amp or 28VAC @ 7 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$106.68	183.93
ALTV2416ULCBI	16 Output Isolated CCTV Power Supply - 24VAC @ 25 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV2416ULCBI3 - Includes factory installed 3-wire line cord.	\$199.78	344.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV2416ULCBX	16 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416ULCBX3 - Includes factory installed 3-wire line cord.	\$108.12	186.42
ALTV2416ULI	16 Output Isolated CCTV Power Supply - 24VAC @ 25 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV2416ULI3 - Includes factory installed 3-wire line cord.	\$199.78	344.44
ALTV2416ULX	16 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2416ULX3 - Includes factory installed 3-wire line cord.	\$108.12	186.42
ALTV2432300UL	32 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2432300UL3 - Includes factory installed 3-wire line cord.	\$174.00	300.00
ALTV2432300ULCB	32 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2432300ULCB3 - Includes factory installed 3-wire line cord.	\$174.00	300.00
ALTV2432350	32 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$174.00	300.00
ALTV2432350CB	32 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$174.00	300.00
ALTV2432600	32 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$200.42	345.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV2432600CB	32 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$200.42	345.56
ALTV2432600UL	32 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2432600UL3 - Includes factory installed 3-wire line cord.	\$200.42	345.56
ALTV2432600ULCB	32 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV2432600UCB3 - Includes factory installed 3-wire line cord.	\$200.42	345.56
ALTV244	4 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$50.65	87.33
ALTV244175	4 Output CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$77.20	133.11
ALTV244175CB	4 Output CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$77.20	133.11
ALTV244175UL	4 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV244175UL3 - Includes factory installed 3-wire line cord.	\$86.23	148.67
ALTV244175ULCB	4 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC Class 2 power limited outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV244175ULCB3 - Includes factory installed 3-wire line cord.	\$86.23	148.67
ALTV244300	4 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$117.29	202.22
ALTV244300CB	4 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$117.29	202.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV244CB	4 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$50.65	87.33
ALTV244UL	4 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV244UL3 - Includes factory installed 3-wire line cord.	\$56.97	98.22
ALTV244ULCB	4 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV244ULCB3 - Includes factory installed 3-wire line cord.	\$56.97	98.22
ALTV248	8 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$62.65	108.02
ALTV248175UL	6 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248175UL2 - Includes factory installed 3-wire line cord.	\$92.16	158.89
ALTV248175ULCB	8 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC Class 2 power limited outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248175ULCB3 - Includes factory installed 3-wire line cord.	\$92.16	158.89
ALTV248300	8 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$130.44	224.89
ALTV248300CB	8 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$130.44	224.89
ALTV248300UL	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248300UL3 - Includes factory installed 3-wire line cord.	\$130.44	224.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV248300ULCB	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248300ULCB3 - Includes factory installed 3-wire line cord.	\$130.44	224.89
ALTV248300ULCBM	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248300ULCBM3 - Includes factory installed 3-wire line cord.	\$123.73	213.33
ALTV248300ULM	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248300ULM3 - Includes factory installed 3-wire line cord.	\$123.73	213.33
ALTV248600	8 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$180.32	310.89
ALTV248600CB	8 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$180.32	310.89
ALTV248600UL	8 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248600UL3 - Includes factory installed 3-wire line cord.	\$180.32	310.89
ALTV248600ULCB	8 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248600ULCB3 - Includes factory installed 3-wire line cord.	\$180.32	310.89
ALTV248CB	8 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$62.65	108.02

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV248UL	8 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248UL3 - Includes factory installed 3-wire line cord.	\$64.08	110.49
ALTV248ULCB	8 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV248ULCB3 - Includes factory installed 3-wire line cord.	\$64.08	110.49
ALTV248ULCBHI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV248ULCBHI3 - Includes factory installed 3-wire line cord.	\$137.27	236.67
ALTV248ULCBMI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV248ULCBMI3 - Includes factory installed 3-wire line cord.	\$132.11	227.78
ALTV248ULHI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV248ULHI3 - Includes factory installed 3-wire line cord.	\$137.27	236.67
ALTV248ULMI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed. ALTV248ULMI3 - Includes factory installed 3-wire line cord.	\$132.11	227.78
ALTV615DC1016	16 Output CCTV Power Supply - 6-15VDC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$161.11	277.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV615DC1016CB	16 Output CCTV Power Supply - 6-15VDC @ 10 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$161.11	277.78
ALTV615DC416UBM	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615D416UBM3 - Includes factory installed 3-wire line cord.	\$110.20	190.00
ALTV615DC416UCB	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC416UC3 - Includes factory installed 3-wire line cord.	\$128.89	222.22
ALTV615DC416UL	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, fuse protected Class 2 Rated power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC416UL3 - Includes factory installed 3-wire line cord.	\$128.89	222.22
ALTV615DC44UCBM	4 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC44UCM3 - Includes factory installed 3-wire line cord.	\$81.84	141.11
ALTV615DC44ULM	4 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC44ULM3 - Includes factory installed 3-wire line cord.	\$81.84	141.11
ALTV615DC48UCBM	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC48UCM3 - Includes factory installed 3-wire line cord.	\$94.73	163.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ALTV615DC48ULM	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC48ULM3 - Includes factory installed 3-wire line cord.	\$94.73	163.33
ALTV615DC4UL	4 Output CCTV Power Supply - 6-12VDC @ 2.5 amp or 12-15VDC @ 2 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 24VAC 40VA or 24VAC 50VA input (Altronix Model# TP2440 or TP2450), UL Listed (UL2044), cUL Listed & CE Approved.	\$62.51	107.78
ALTV615DC616UCB	16 Output CCTV Power Supply - 6-15VDC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC616UC3 - Includes factory installed 3-wire line cord.	\$141.78	244.44
ALTV615DC616UL	16 Output CCTV Power Supply - 6-15VDC @ 6 amp, fuse protected non power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC616UL3 - Includes factory installed 3-wire line cord.	\$141.78	244.44
ALTV615DC8UL	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC8UL3 - Includes factory installed 3-wire line cord.	\$116.00	200.00
ALTV615DC8ULCB	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved. ALTV615DC8ULCB3 - Includes factory installed 3-wire line cord.	\$116.00	200.00
AT4	4 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Four SPDT contacts rated @ 10 amp/115VAC/28VDC, 254 daily/weekly events, 1778 weekly block events, 254 holiday exceptions, LCD display, built-in battery charger, encl. 12.25"H x 7.75"W x 4.5"D.	\$161.11	277.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
AT4B	4 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Four SPDT contacts rated @ 10 amp/115VAC/28VDC, 254 daily/weekly events, 1778 weekly block events, 254 holiday exceptions, LCD display, built-in battery charger.	\$148.22	255.56
BC100	Enclosure - 8.5"H x 7.5"W x 3.5"D, 19 gauge steel. Fits 2 - 12VDC/4AH batteries or 1 - 12VDC/7AH battery.	\$21.91	37.78
BC1240	Enclosure - 9.5"H x 9.5"W x 7.5"D, 19 gauge steel, includes cam lock. Accommodates 1 - 12VDC/40AH battery.	\$50.91	87.78
BC200	Enclosure - 12.25"H x 7.75"W x 4.5"D, 19 gauge steel. Fits up to 2 - 12VDC/7AH batteries.	\$27.07	46.67
BC300	Enclosure - 13.5"H x 13"W x 3.25"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/7AH batteries.	\$37.38	64.44
BC300R	Red Enclosure - 13.5"H x 13"W x 3.25"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/7AH batteries.	\$37.38	64.44
BC400	Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	\$54.13	93.33
BC400R	Red Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	\$54.13	93.33
BC400SG	Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes battery shelf (BCS4G) & cam lock. Fits up to 4 - 12VDC/12AH batteries.	\$74.76	128.89
BC400SR	Red Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes battery shelf (BCS4R) & cam lock. Fits up to 4 - 12VDC/12AH batteries.	\$74.76	128.89
BC600	Red Enclosure - 18"H x 14.5"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	\$69.60	120.00
BC600G	Enclosure - 18"H x 14.5"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	\$69.60	120.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
BC800	Enclosure - 26"H x 19"W x 6.25"D, 16 gauge steel, includes cam lock. Mounting provided for up to 2 - power supply/chargers & up to 3 - optional accessory modules, fits up to 4 - 12VDC/12AH batteries	\$209.01	360.36
BC901MY	Enclosure accommodates various combinations of Mercury Boards for systems up to twelve (12) doors or in combination with Altronix Power Supply/Chargers for up to eight (8) doors, and one MRDT Keypad. Enclosure dimensions 27.25"H x 19"W x 6.5"D.	\$187.21	322.78
BC902MY	Enclosure accommodates various combinations of Mercury Boards for systems up to twenty four (24) doors or in combination with Altronix Power Supply/Chargers for up to sixteen (16) doors, and one MRDT Keypad. Enclosure dimensions 27.25"H x 19"W x 6.5"D. Includes one Cam Lock, one Tamper Switch and 100 Standoffs and Screws .	\$203.64	351.11
BCS4G	Battery shelf for BC400 encl.	\$19.33	33.33
BCS4R	Red battery shelf for BC400R encl.	\$19.33	33.33
BF10	Blade Fuse 10 amp (red). Package of 25.	\$11.28	19.44
BF15	Blade Fuse 15 amp (blue). Package of 25.	\$9.67	16.67
BF3	Blade Fuse 3 amp (violet). Package of 25.	\$9.67	16.67
BF5	Blade Fuse 5 amp (brown). Package of 25.	\$9.67	16.67
BL2	2 - 8" Battery leads (Red & Black).	\$0.64	1.11
BL3	2 - 18" Battery leads (Red & Black).	\$1.29	2.22
BL4	1 - 8" Battery Jumper (Yellow).	\$1.29	2.22
BNC24J	Coax Jumper 24" Male to Male.	\$3.61	6.23
BT1212	Lead Acid Battery - 12VDC/12AH, Dimensions 3.5"H x 5.94"W x 3.75"D.	\$46.40	80.00
BT124	Lead Acid Battery - 12VDC/4AH, Dimensions 4"H x 3.5"W x 2.76"D.	\$16.43	28.33
BT1240	Lead Acid Battery - 12VDC/40AH, Dimensions 6.73"H x 7.72"W x 6.5"D.	\$113.10	195.00
BT126	Lead Acid Battery - 12VDC/7AH, Dimensions 3.66"H x 5.94"W x 2.56"D.	\$20.62	35.56
CAB4	Enclosure - 5.625"H x 7"W x 4.5"D, 19 gauge steel. Accommodates 1 - 12VDC/12AH battery.	\$32.22	55.56
CAM1	Cam lock w/mounting hardware.	\$3.87	6.67
CLIP1	2 - DIN Rail Mounting Clips.	\$4.51	7.78
CP1	Conversion plate for mounting two (2) PD4/PD8 or two (2) MOM5 boards in BC400/BC400R enclosure.	\$9.02	15.56
D10	1 - 10" length of DIN Rail.	\$3.87	6.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
DK1	1 - DIN Rail Mount Kit - 1 piece of Snap Track and two (2) DIN Rail Mounting Clips.	\$12.89	22.22
DL 3	Door Control Timer w/sounder - 12 to 24 Volt AC or DC operation, SPDT contact rated @ 3 amp/120VAC/28VDC, Use with magnetic locks & electric strikes.	\$38.66	66.66
DL1	Door Control Timer - 12 to 24 Volt AC or DC operation, SPDT contact rated @ 3 amp/120VAC/28VDC, Use with magnetic locks & electric strikes.	\$29.77	51.33
DP4	DIN Rail Mountable 4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs. Includes Snap Track & mounting clips.	\$30.93	53.33
DPS1	DIN Rail Mount Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, Includes snap track & mounting clips (order DIN Rail separately).	\$19.10	32.93
DPS3	DIN Rail Mount Power Supply/Charger - 6VDC, 12VDC or 24VDC rated @ 2.5 amp, Includes snap track & mounting clips (order DIN Rail separately).	\$36.28	62.56
DPS5	DIN Rail Mount Power Supply/Charger - 6VDC, 12VDC or 24VDC rated @ 4 amp, Includes snap track & mounting clips (order DIN Rail separately).	\$49.56	85.44
DPT724A	DIN Rail Mountable Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 365 day/24 hr. timer, LCD display, Programmable features: 50 individual daily/weekly events, 350 block events per week, 10 holiday dates.	\$80.56	138.89
DTMR1	DIN Rail Mountable Multi-Function Timer - 12VDC or 24VDC operation, SPDT contacts rated @ 8 amp/115VAC, 1 sec. to 60 min. adjustable timing range. One second momentary relay activation at the end of timing cycle, Includes Snap Track & mounting clips.	\$29.90	51.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EBRIDGE100RM	Ethernet over coax/CAT5e Receiver. Transmits IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Requires eBridge100TM. UL/cUL Listed (UL60950-1). CE Approved.	\$127.60	220.00
EBRIDGE100RMT	Ethernet over coax/CAT5e Receiver/Transceiver adapter kit - Transmits IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). UL/cUL Listed (UL60950-1). CE Approved.	\$255.20	440.00
EBRIDGE100SPR	56VDC/100W Ethernet over coax receiver compatible with eBridge200WPM 2-port Transceiver. 100mbps full duplex	\$127.60	220.00
EBRIDGE100TM	Ethernet over coax/CAT5e Transceiver. Transmits IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge100RM, eBridge400PCRM, eBridge800PCRM and eBridge1600PCRM. UL/cUL Listed (UL60950-1). CE Approved.	\$127.60	220.00
EBRIDGE1600PCRM	16-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 300m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge100TM transceiver. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	#####	3732.22
EBRIDGE16CR	16-Port Ethernet over coax Receiver transmits IP video/data over coax up to 500m @ 25mbps. Compatible with eBridge1CT and devices incorporating sloc technology. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	#####	3390.00
EBRIDGE16PCRM	16-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge1PCT and eBridge1PCTX transceivers. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	#####	3390.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EBRIDGE16PCRX	16-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Browser based power management and local or remote status monitoring. Compatible with eBridge1PCT and eBridge1PCTX transceivers. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	#####	3390.00
EBRIDGE1CR	Ethernet over coax adapter Receiver. Provides IP video/data over coax up to 500m @ 25mbps. Compatible with eBridge1CT and devices incorporating sloc technology. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$95.58	164.80
EBRIDGE1CRT	Ethernet over coax adapter kit. Receiver/Transceiver transmits IP video/data over coax up to 500m @ 25mbps. UL/cUL Listed (UL60950-1). CE Approved.	\$181.60	313.10
EBRIDGE1CT	Ethernet over coax Transceiver. Transmits IP video/data over coax up to 500m @ 25mbps. Compatible with any eBridge receivers. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$95.58	164.80
EBRIDGE1PCR	Ethernet over coax Receiver. Provides IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Requires eBridge1PCT. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$122.44	211.10
EBRIDGE1PCRM	Ethernet over coax Receiver. Provides IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge1PCT and eBridge1PCTX transceivers. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$122.44	211.10
EBRIDGE1PCRMT	Ethernet over coax adapter kit. Receiver/Transceiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). UL/cUL Listed (UL60950-1). CE Approved.	\$226.84	391.10
EBRIDGE1PCRT	Ethernet over coax adapter kit. Receiver/Transceiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af). UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$226.84	391.10

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EBRIDGE1PCRTX	Ethernet over coax adapter kit. Receiver/Transceiver transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). UL/cUL Listed (UL60950-1). CE Approved.	\$226.84	391.10
EBRIDGE1PCRX	Ethernet over coax Receiver. Provides IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Requires eBridge1PCT or eBridge1PCTX. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$122.44	211.10
EBRIDGE1PCT	Ethernet over coax Transceiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af). Compatible with eBridge1PCR, eBridge1PCRX, eBridge4PCRM, eBridge4PCRX, eBridge8PCRM, eBridge8PCRX, eBridge16PCRM and eBridge16PCRX receivers. UL/cUL Listed (UL60950-1). CE Approved.	\$114.72	197.80
EBRIDGE1PCTX	Ethernet over coax Transceiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge1PCR, eBridge4PCRM, eBridge4PCRX, eBridge8PCRM, eBridge8PCRX, eBridge16PCRM and eBridge16PCRX receivers. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$114.72	197.80
EBRIDGE1SPR	56VDC/100W Ethernet over coax receiver compatible with eBridge4SPT 4-port Transceiver. 25Mbps throughput. CE and C-Tick Approved.	\$101.82	175.56
EBRIDGE100ST	Ethernet over coax/CAT5e Mini Transceiver. Transmits IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge100PCM, eBridge400PCRM, eBridge800PCRM	\$127.60	220.00
EBRIDGE100STR	Ethernet over coax/CAT5e Receiver/Mini Transceiver adapter kit - Transmits IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE	\$255.20	440.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EBRIDGE200WPM	2-Port Ethernet over coax/CAT5e Transceiver. Provides IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at) or Hi-PoE (60W). Use with eBridge100SPR, Pace1PRD, NetWay1D, any Midspan or Endspan. NEMA 4/4X/IP66-11 rated enclosure 9.5"H x 7.32"W x 4.92"D. UL/cUL Listed (UL60950-1). CE Approved.	\$248.76	428.89
EBRIDGE200WPMH	2-Port Ethernet over coax/CAT5e Transceiver. Provides IP video/data over coax up to 300m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at) or Hi-PoE (60W). Use with eBridge100SPR, Pace1PRD, NetWay1D, any Midspan or Endspan. NEMA 4/4X/IP66-11 rated enclosure 9.5"H x 7.32"W x 4.92"D with three (3) 5/8" wiring inlets, includes NEMA rated glands. UL/cUL Listed (UL60950-1). CE Approved.	\$252.62	435.56
EBRIDGE400PCRM	4-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 300m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge100TM transceiver. UL/cUL Listed (UL60950-1). CE Approved.	\$510.72	880.56
EBRIDGE4CR	4-Port Ethernet over coax Receiver transmits IP video/data over coax up to 500m @ 25mbps. Compatible with eBridge1CT and devices incorporating sloc technology. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$461.10	795.00
EBRIDGE4PCRM	4-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge1PCT and eBridge1PCTX transceivers. UL/cUL Listed (UL60950-1). CE Approved.	\$461.10	795.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EBRIDGE4PCRX	4-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Browser based power management and local or remote status monitoring. Compatible with eBridge1PCT and eBridge1PCTX transceivers. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$461.10	795.00
EBRIDGE4SK	4-Port PoE/PoE+ EoC Transceiver Switch with EoC Receiver Kit - each port supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Total power 95W. Built-in IP management facilitates programming and status monitoring via laptop or LAN. UL/cUL Listed (UL60950-1). CE Approved.	\$411.16	708.89
EBRIDGE800PCRM	8-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 300m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge100TM transceiver. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	#####	1866.11
EBRIDGE8PCRM	8-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with eBridge1PCT and eBridge1PCTX transceivers. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	\$983.10	1695.00
EBRIDGE8PCRX	8-Port Ethernet over coax Receiver. Transmits IP video/data over coax up to 500m @ 25mbps and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Browser based power management and local or remote status monitoring. Compatible with eBridge1PCT and eBridge1PCTX transceivers. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	\$983.10	1695.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW102N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max, One (1) aux. output (unswitched) plus one (1) aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$218.47	376.67
EFLOW102N16	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$249.40	430.00
EFLOW102N16D	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$249.40	430.00
EFLOW102N8	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$233.93	403.33
EFLOW102N8D	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power	\$233.93	403.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW102NA8	Power Supply/Charger with Access power controller - 8 fused outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$267.44	461.11
EFLOW102NA8D	Power Supply/Charger with Access power controller - 8 PTC power-limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$267.44	461.11
EFLOW102NB	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max, additional separate 1 amp aux. Class 2 rated power-limited output, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), 115VAC input, UL Recognized, cUL Listed.	\$166.91	287.78
EFLOW102NX	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$222.33	383.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW102NX16	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$253.27	436.67
EFLOW102NX16D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$253.27	436.67
EFLOW102NX8	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$237.80	410.00
EFLOW102NX8D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$237.80	410.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW104N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$244.24	421.11
EFLOW104N16	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$275.18	474.44
EFLOW104N16D	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$275.18	474.44
EFLOW104N8	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$259.71	447.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW104N8D	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$259.71	447.78
EFLOW104NA8	Power Supply/Charger with Access power controller - 8 fused outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$293.22	505.56
EFLOW104NA8D	Power Supply/Charger with Access power controller - 8 PTC power-limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$293.22	505.56
EFLOW104NB	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max, additional separate 1 amp aux. Class 2 rated power-limited output, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), 115VAC input, UL Recognized, cUL Listed.	\$192.69	332.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW104NX	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$248.11	427.78
EFLOW104NX16	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$279.04	481.11
EFLOW104NX16D	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D	\$279.04	481.11
EFLOW104NX8	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$263.58	454.44
EFLOW104NX8D	Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$263.58	454.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW3N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$159.82	275.56
EFLOW3N4	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max. Four (4) fused Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$172.71	297.78
EFLOW3N4D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max. Four (4) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$172.71	297.78
EFLOW3NB	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max, additional separate 1 amp aux. Class 2 rated power-limited output, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), 115VAC input, UL Recognized, cUL Listed.	\$121.80	210.00
EFLOW3NX	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$163.69	282.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW3NX4	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max. Four (4) fused Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$176.58	304.44
EFLOW3NX4D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max. Four (4) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$176.58	304.44
EFLOW4N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$167.56	288.89
EFLOW4N8	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max. Eight (8) fused Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$183.02	315.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW4N8D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$183.02	315.56
EFLOW4NA8	Power Supply/Charger with Access power controller - 8 fused power-limited outputs provide 12VDC or 24VDC @ 4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$216.53	373.33
EFLOW4NA8D	Power Supply/Charger with Access power controller - 8 PTC power-limited outputs provide 12VDC or 24VDC @ 4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$216.53	373.33
EFLOW4NB	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max, additional separate 1 amp aux. Class 2 rated power-limited output, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), 115VAC input, UL Recognized, cUL Listed.	\$140.81	242.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW4NX	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$171.42	295.56
EFLOW4NX8	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max. Eight (8) fused Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$186.89	322.22
EFLOW4NX8D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 4 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$186.89	322.22
EFLOW6N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$218.47	376.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW6N16	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$249.40	430.00
EFLOW6N16D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$249.40	430.00
EFLOW6N8	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$233.93	403.33
EFLOW6N8D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 13.5"H x 13"W x 3.25"D accommodates up to (2) 12VDC/7AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$233.93	403.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW6NA8	Power Supply/Charger with Access power controller - 8 fused outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$267.44	461.11
EFLOW6NA8D	Power Supply/Charger with Access power controller - 8 PTC power-limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), ULC Listed (ULC-S319-05).	\$267.44	461.11
EFLOW6NB	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max, additional separate 1 amp aux. Class 2 rated power-limited output, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), 115VAC input, UL Recognized, cUL Listed.	\$166.91	287.78
EFLOW6NX	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max, One (1) main power output (unswitched) plus one (1) separate aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved	\$222.33	383.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
EFLOW6NX16	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Sixteen (16) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$253.27	436.67
EFLOW6NX16D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Sixteen (16) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$253.27	436.67
EFLOW6NX8	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Eight (8) fused outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$237.80	410.00
EFLOW6NX8D	Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp max. Eight (8) PTC Class 2 power-limited outputs and one (1) aux. power output, AC & battery monitoring, Low battery cutoff, Over voltage protection, encl. 15.5"H x 12"W x 4.5"D accommodates up to (2) 12VDC/12AH batteries, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96). CSFM, CE Approved.	\$237.80	410.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
ENTRADA2DMK	IP Access FACP Adapters. Facilitates emergency egress without deploying additional cable. Supervised fire alarm disconnect releases locking devices while maintaining power to the network door controller(s). Accommodate up to two (2) 12/24VDC strikes or mag locks. A single FACP input will trigger multiple units. Supports PoE+ edge devices. UL/cUL Listed (UL60950-1), UL Listed (UL294/UL294B)	\$186.24	321.11
FIRESWITCH108	Managed NAC Power Extender - 24VDC @ 10 amp. 4 Class A or 8 - Class B NAC circuits, 8 aux. outputs or any combination, Ethernet port facilitates programming and status monitoring via laptop or LAN, LCD display, operates 2-wire Horn/Strobes, Built-in sync protocols, two - 1 amp aux. outputs, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL864), ULC Listed (ULC-S527-99), CSFM.	\$380.22	655.55
FUSE1	Glass fuse - 3.5 amp (3AG). Package of 100	\$32.22	55.56
FUSE2	Glass fuse - 5 amp (3AG). Package of 100	\$32.22	55.56
FUSE3	Glass fuse - 10 amp (3AG). Package of 100	\$32.22	55.56
FUSE4	Glass fuse - 1 amp (3AG). Package of 100	\$32.22	55.56
FUSE5	Glass fuse - 5 amp slow blow (3AG). Package of 100	\$38.66	66.66
GL1	1 - 8" Ground Lead (Green).	\$0.64	1.11
HUBSAT42D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$230.72	397.80
HUBSAT42DI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	\$235.22	405.55

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBSAT42WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	\$281.75	485.78
HUBSAT42WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	\$286.26	493.55
HUBSAT43D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$257.14	443.35
HUBSAT43DI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	\$261.64	451.10
HUBSAT43WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	\$308.18	531.34
HUBSAT43WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	\$312.69	539.12

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBSAT4D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$174.00	300.00
HUBSAT4DI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input.	\$178.51	307.78
HUBSAT4WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input.	\$225.04	388.00
HUBSAT4WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input.	\$229.55	395.78
HUBSAT82D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$442.09	762.22
HUBSAT82DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, includes 8 HubWayAv Video Balun/Combiners for 24VAC cameras.	\$451.11	777.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBSAT83D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$494.93	853.33
HUBSAT83DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, includes 8 HubWayDv Video Balun/Combiners for 12VDC cameras.	\$503.96	868.89
HUBSAT8D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$328.67	566.67
HUBSAT8DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input.	\$337.69	582.23
HUBWAY162CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$939.60	1620.00
HUBWAY162D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$939.60	1620.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAY162DI	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	#####	1886.67
HUBWAY163CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	1795.56
HUBWAY163D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	1795.56
HUBWAY163DI	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	2062.22
HUBWAY16CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$708.91	1222.25

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAY16D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$708.91	1222.25
HUBWAY16DI	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	\$863.56	1488.89
HUBWAY82CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$467.87	806.67
HUBWAY82CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$467.87	806.67
HUBWAY82D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$467.87	806.67
HUBWAY82DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed	\$545.20	940.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAY82DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$467.87	806.67
HUBWAY83CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$520.71	897.78
HUBWAY83CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$520.71	897.78
HUBWAY83D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$520.71	897.78
HUBWAY83DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed	\$598.04	1031.11

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAY83DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$520.71	897.78
HUBWAY8CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$354.44	611.11
HUBWAY8CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$354.44	611.11
HUBWAY8D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$354.44	611.11
HUBWAY8DI	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$431.78	744.45
HUBWAY8DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$354.44	611.11
HUBWAYAV	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable, UL Listed.	\$16.76	28.89
HUBWAYAV2	Slim-line Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable	\$16.76	28.89
HUBWAYAV2PK	HubWayAv2 eight (8) pack	\$114.71	197.78
HUBWAYAVP	Slim-line Video Balun/Combiner - Video/Power over a single CAT-5 cable	\$16.76	28.89
HUBWAYAVPK	HubWayAv eight (8) pack	\$114.71	197.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYAVPPK	HubWayAvP eight (8) pack	\$114.71	197.78
HUBWAYDV	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable for 12VDC Fixed or PTZ cameras, UL Listed.	\$24.49	42.22
HUBWAYDVI	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable for non-isolated 12VDC Fixed or PTZ cameras, UL Listed.	\$30.29	52.22
HUBWAYDVIPK	HubWayDvi eight (8) pack	\$205.58	354.45
HUBWAYDVPK	HubWayDv eight (8) pack	\$166.26	286.65
HUBWAYEX1	Single Port Active UTP Transceiver Module. Video/Data up to one mile. Automatic Picture and Gain control. High Impact Insulated Housing. 6VAC-24VAC or 12VDC-24VDC input, UL Listed (UL2044), cUL Listed.	\$96.66	166.65
HUBWAYEX16	Active UTP Transceiver Hub. Allows video transmission of up to 16 cameras over four (4) Cat 5 cables. Video up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	2208.90
HUBWAYEX16S	16 Port Active UTP Transceiver Hub. Video/Data up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	2208.90
HUBWAYEX16SP	16 Port Active UTP Transceiver Hub w/Isolated Integral camera power. Individually selectable for 24VAC or 28VAC at 1 amp per port. Video/Data up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	2670.56
HUBWAYEX32	Active UTP Transceiver Hub. Allows video transmission of up to 32 cameras over eight (8) Cat 5 cables. Video up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	4333.35
HUBWAYEXP	UTP Power Injector, 16 Isolated Power Ports. Individually selectable for 24VAC or 28VAC at 1 amp per port with pass-through video and data. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	\$451.12	777.80

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYH16	16 Channel Passive UTP Transceiver Hub, allows Video, remote power and PTZ control to be transmitted over a single CAT-5e/6 cable, individual channels are selectable for video/PTZ control/power or video and power only, 1U EIA 19" Rack Mount Chassis	\$283.56	488.90
HUBWAYLD162CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	#####	2439.45
HUBWAYLD162D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	#####	2439.45
HUBWAYLD162DI	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	#####	2706.11
HUBWAYLD163CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	2621.70

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYLD163D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	2621.70
HUBWAYLD163DI	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	#####	2888.33
HUBWAYLD16CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	#####	2048.35
HUBWAYLD16D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	#####	2048.35
HUBWAYLD16DI	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	2315.00
HUBWAYLD82CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$785.90	1355.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYLD82CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$785.90	1355.00
HUBWAYLD82D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$785.90	1355.00
HUBWAYLD82DI	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$863.23	1488.33
HUBWAYLD82DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	\$785.90	1355.00
HUBWAYLD83CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$838.74	1446.11

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYLD83CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$838.74	1446.11
HUBWAYLD83D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$838.74	1446.11
HUBWAYLD83DI	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$916.08	1579.44
HUBWAYLD83DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	\$838.74	1446.11
HUBWAYLD8CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$672.48	1159.45
HUBWAYLD8CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	\$672.48	1159.45

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
HUBWAYLD8D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$672.48	1159.45
HUBWAYLD8DI	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$749.81	1292.78
HUBWAYLD8DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	\$672.48	1159.45
HUBWAYLDH16	16 Channel Active UTP Transceiver Hub, Video/Data up to 3000 ft., 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	#####	1853.35
HUBWAYLDH8	8 Channel Active UTP Transceiver Hub, Video/Data up to 3000 ft., 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	\$559.38	964.45
LB2032	1 - Lithium battery (3v) for AT4, PT2724, PT724A & PT724AE.	\$2.58	4.44
LC1	6 ft. 2-Wire Line Cord.	\$1.55	2.67
LC2	6 ft. Grounded 3-Wire Line Cord.	\$3.22	5.56
LINQ2	Network Communication Module. Designed for use with up to two (2) Altronix eFlow series power supplies. Allows for status monitoring via LAN/WAN of (DC output voltage, Output Current, AC fault,	\$83.78	144.44
LPD	Low Power Disconnect Module - 12VDC/24VDC input, Disconnects at 10.5 volts (12 volt setting), 20 volts (24 volt setting)	\$10.31	17.78
LPS3	Linear Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, 5 amp on demand.	\$37.89	65.33
LPS3AC	Linear Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, 5 amp on demand, AC monitoring.	\$51.56	88.89
LPS3C12X	Linear Power Supply/Charger - 12VDC @ 2.5 amp, 5 amp on demand, encl. 13.5"H x 13"W x 3.25"D.	\$121.80	210.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
LPS3C24X	Linear Power Supply/Charger - 24VDC @ 2.5 amp, 5 amp on demand, encl. 13.5"H x 13"W x 3.25"D.	\$121.80	210.00
LPS3WP12	Linear Power Supply/Charger - 12VDC @ 2.5 amp, 5 amp on demand, NEMA4/IP65 rated outdoor encl. 12"H x 8"W x 6"D, 115VAC input.	\$173.36	298.89
LPS3WP24	Linear Power Supply/Charger - 24VDC @ 2.5 amp, 5 amp on demand, NEMA4/IP65 rated outdoor encl. 12"H x 8"W x 6"D, 115VAC input.	\$173.36	298.89
LPS5C12X	Linear Power Supply/Charger - 12VDC @ 3.5 amp, 8 amp on demand, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$140.49	242.22
LPS5C24X	Linear Power Supply/Charger - 24VDC @ 3.5 amp, 8 amp on demand, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$140.49	242.22
MAXIMAL11	2 Power Supply/Chargers with Access power controllers - 16 fused Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.5 amp or 24VDC @ 2.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$418.89	722.22
MAXIMAL11D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.5 amp or 24VDC @ 2.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$418.89	722.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL11E	2 Power Supply/Chargers - Each are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$322.22	555.56
MAXIMAL11F	2 Power Supply/Chargers with Access power controllers - 16 fused power-limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.3 amp or 24VDC @ 3.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$457.56	788.89
MAXIMAL11FD	2 Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.3 amp or 24VDC @ 3.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$457.56	788.89
MAXIMAL11FE	2 Power Supply/Chargers - Each are selectable for 12VDC or 24VDC @ 4 amp, power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$360.89	622.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL13E	2 Power Supply/Chargers - One is selectable for 12VDC @ 4 amp or 24VDC @ 3 amp Class 2 power limited output and One is selectable for 12VDC or 24VDC @ 6 amp non-power limited output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$332.53	573.33
MAXIMAL13FE	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 4 amp, power-limited output and one is 12VDC or 24VDC @ 6 amp, non power-limited output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$371.20	640.00
MAXIMAL1R	Power Supply/Charger with Access power controllers - 16 fused outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$337.04	581.11
MAXIMAL1RD	Power Supply/Charger with Access power controllers - 16 PTC outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$337.04	581.11

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL1RH	Power Supply/Charger with Access power controllers - 8 fused outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$297.73	513.33
MAXIMAL1RHD	Power Supply/Charger with Access power controllers - 8 PTC outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$297.73	513.33
MAXIMAL3	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs can be selected for 12VDC or 24VDC @ 5.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$401.49	692.22
MAXIMAL33	2 Power Supply/Chargers with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.5 amp or 24VDC @ 5.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$514.91	887.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL33D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.5 amp or 24VDC @ 5.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$514.91	887.78
MAXIMAL33E	2 Power Supply/Chargers - Each are selectable for 12VDC or 24VDC @ 6 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$386.67	666.67
MAXIMAL33F	2 Power Supply/Chargers with Access power controllers - 16 fused non power-limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.3 amp or 24VDC @ 5.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$553.58	954.44
MAXIMAL33FD	2 Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.3 amp or 24VDC @ 5.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$553.58	954.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL33FE	2 Power Supply/Chargers - Each are 12VDC or 24VDC @ 6 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$425.33	733.33
MAXIMAL33R	2 Power Supply/Chargers with Access power controllers - 16 fused outputs, each set of 8 outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$543.27	936.67
MAXIMAL33RD	2 Power Supply/Chargers with Access power controllers - 16 PTC outputs, each set of 8 outputs are selectable for 12VDC or 24VDC @ 6 amp (12 amp max.), outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$543.27	936.67
MAXIMAL35E	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and One is selectable for 12VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$386.67	666.67
MAXIMAL35FE	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and one is 12VDC @ 10 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$425.33	733.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL37E	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and one is 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$424.04	731.11
MAXIMAL37FE	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and one is 24VDC @ 10 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$462.71	797.78
MAXIMAL3D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs can be selected for 12VDC or 24VDC @ 5.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$401.49	692.22
MAXIMAL3F	Power Supply/Charger with Access power controllers - 16 fused non power-limited outputs, 16 outputs can be selected for 12VDC @ 4.6 amp or 24VDC @ 5.2 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D	\$420.82	725.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL3FD	Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, 16 outputs can be selected for 12VDC @ 4.6 amp or 24VDC @ 5.2 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$420.82	725.56
MAXIMAL3R	Power Supply/Charger with Access power controllers - 16 fused outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$362.82	625.55
MAXIMAL3RD	Power Supply/Charger with Access power controllers - 16 PTC outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$362.82	625.55
MAXIMAL3RH	Power Supply/Charger with Access power controllers - 8 fused outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$323.52	557.80
MAXIMAL3RHD	Power Supply/Charger with Access power controllers - 8 PTC outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$323.52	557.80

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL5	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs are 12VDC @ 9 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$407.93	703.33
MAXIMAL55	2 Power Supply/Chargers with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs is 12VDC @ 9.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$514.91	887.78
MAXIMAL55D	2 Power Supply/Charger with Access power controllers - 16 PTC power limited outputs, each set of 8 outputs is 12VDC @ 9.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$514.91	887.78
MAXIMAL55E	2 Power Supply/Chargers - Each are 12VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	\$386.67	666.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL55F	2 Power Supply/Chargers with Access power controllers - 16 fused non power-limited outputs, each set of 8 outputs is 12VDC @ 9.3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$553.58	954.44
MAXIMAL55FD	2 Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, each set of 8 outputs is 12VDC @ 9.3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$553.58	954.44
MAXIMAL55FE	2 Power Supply/Chargers - Each are 12VDC @ 10 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$425.33	733.33
MAXIMAL5D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs are 12VDC @ 9 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$407.93	703.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL5F	Power Supply/Charger with Access power controllers - 16 fused non power-limited outputs, 16 outputs are 12VDC @ 8.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$427.27	736.67
MAXIMAL5FD	Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, 16 outputs are 12VDC @ 8.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$427.27	736.67
MAXIMAL7	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs are 24VDC @ 9.4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$433.71	747.78
MAXIMAL75	2 Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 8 outputs are 12VDC @ 9.5 amp and 8 outputs are 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$540.69	932.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL75D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 8 outputs are 12VDC @ 9.5 amp and 8 outputs are 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$540.69	932.22
MAXIMAL75E	2 Power Supply/Chargers - One is 12VDC @ 10 amp and one is 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed.	\$412.44	711.11
MAXIMAL75F	2 Power Supply/Charger with Access power controllers - 16 fused non power-limited outputs, 8 outputs are 12VDC @ 9.3 amp and 8 outputs are 24VDC @ 9.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D	\$579.36	998.89
MAXIMAL75FD	2 Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, 8 outputs are 12VDC @ 9.3 amp and 8 outputs are 24VDC @ 9.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$579.36	998.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL75FE	2 Power Supply/Chargers - One is 12VDC @ 10 amp and one is 24VDC @ 10 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$451.11	777.78
MAXIMAL77	2 Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs is 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL 294), cUL Listed, CSFM Approved.	\$566.47	976.67
MAXIMAL77D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs is 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$566.47	976.67
MAXIMAL77E	2 Power Supply/Chargers - Each are 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input	\$438.22	755.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL77F	2 Power Supply/Charger with Access power controllers - 16 fused non power-limited outputs, each set of 8 outputs is 24VDC @ 9.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$605.13	1043.33
MAXIMAL77FD	2 Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, each set of 8 outputs is 24VDC @ 9.6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$605.13	1043.33
MAXIMAL77FE	2 Power Supply/Chargers - Each are 24VDC @ 10 amp, non power-limited outputs, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$476.89	822.22
MAXIMAL7D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs are 24VDC @ 9.4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	\$433.71	747.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
MAXIMAL7F	Power Supply/Charger with Access power controllers - 16 fused non power-limited outputs, 16 outputs are 24VDC @ 9.2 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$453.04	781.11
MAXIMAL7FD	Power Supply/Charger with Access power controllers - 16 PTC power-limited outputs, 16 outputs are 24VDC @ 9.4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, Features: Low battery cutoff, Over voltage protection (OVP), AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed (ULC-S319-05), CSFM Approved.	\$453.04	781.11
MOM5	5 Output Access Power Distribution Module - Converts one (1) 12VDC or 24VDC input into five (5) power outputs, PTC Class 2 power limited outputs rated @ 2.5 amp, Fire Alarm interface, UL Recognized.	\$25.78	44.44
MOM5C	5 Output Access Power Distribution Module - Converts one (1) 12VDC or 24VDC input into five (5) power outputs, PTC Class 2 power limited outputs rated @ 2.5 amp, Fire Alarm interface, encl. 8"H x 7.25"W x 3.5"D. UL Listed (UL294/UL1481), CSFM & MEA Approved.	\$47.69	82.22
NETWAY1	Single Port Midspan PoE Injector 24VAC/24VDC operation - PoE compliant port is rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing, UL/cUL Listed (UL60950-1), UL Listed (UL294), CE and C-Tick Approved.	\$41.24	71.11

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
NETWAY112	Single Port Midspan PoE Injector 12VDC operation - PoE compliant port is rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE approved.	\$41.24	71.11
NETWAY1512	12VDC/13W NetWay midspan adapter for IP cameras and devices, UL/cUL Listed (UL60950-1).	\$42.53	73.33
NETWAY16	16-Port Midspan - each port provides PoE (IEEE 802.3af) compliant. Total power 300W. 1U EIA 19" Rack Mount Chassis. 115VAC Input. UL/cUL Listed (UL60950-1), UL Listed (UL294).	\$534.24	921.10
NETWAY16M	16-Port Managed Midspan - each port provides PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at) compliant. Total power 300W, PoE shutdown selectable by port. Ethernet port facilitates programming and status monitoring via laptop or LAN. 1U EIA 19" Rack Mount Chassis. 115VAC Input. UL/cUL Listed (UL60950-1), UL Listed (UL294) .	\$572.91	987.78
NETWAY1D	Single Port Midspan Injector/Power Supply - Provides Hi-PoE (60W), PoE (15.4W), PoE+ (30W) or 56VDC@60W (Class 2 rated power-limited output), 115/230VAC Input, UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$104.40	180.00
NETWAY1DWP	Outdoor Single Port Midspan Injector - Provides Hi-PoE (60W), PoE (15.4W) and PoE+ (30W) compliant, 115/230VAC Input, NEMA 4/4X/IP66-11 rated enclosure 9.5"H x 7.32"W x 4.92"D. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$206.22	355.56
NETWAY1DWPB	Outdoor Single Port Midspan Injector - Hi-PoE (60W), PoE (15.4W) compliant, PoE+ (30W) compliant, 115/230VAC Input, NEMA 4/4X/IP66-11 rated enclosure 9.5"H x 7.32"W x 4.92"D with three (3) 5/8" wiring inlets, includes NEMA rated glands. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$210.09	362.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
NETWAY1DWPM	Outdoor Managed Single Port Midspan Injector - Provides High-PoE (60W), PoE (15.4W) or PoE+ (30W). IP management facilitates programming and status monitoring via LAN/WAN, NEMA 4/4X/IP66 rated enclosure 9.5"H x 7.32"W x 4.92"D. 115/230VAC Input. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$235.87	406.67
NETWAY1DWPMH	Outdoor Managed Single Port Midspan Injector - Provides Hi-PoE (60W), PoE (15.4W) compliant, PoE+ (30W) compliant. IP management facilitates programming and status monitoring via LAN/WAN, 115/230VAC Input, NEMA 4/4X/IP66-11 rated enclosure 9.5"H x 7.32"W x 4.92"D with three (3) 5/8" wiring inlets, includes NEMA rated glands. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$239.73	413.33
NETWAY1E	Single Port Midspan Injector - Provides PoE (15.4W) or PoE+(30W), PoE shutdown feature, 115VAC Input, UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$148.22	255.56
NETWAY1EV	Single Port Midspan Injector - Single port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at, PoE shutdown feature, 230VAC Input, UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$148.22	255.56
NETWAY1P	Single Port Midspan Injector - One PoE compliant port rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing, UL/cUL Listed (UL60950-1), UL Listed (UL294). Includes TP2440 Plug-in transformer 24VAC/40VA, 115VAC input, UL Listed.	\$52.84	91.10
NETWAY1X	Single Port Midspan Injector - PoE (15.4W) or PoE+ (30W), PoE shutdown feature. 24VAC/24VDC input. UL/cUL Listed (UL60950-1), CE and C-Tick Approved.	\$50.27	86.67
NETWAY1XP	Single Port Midspan Injector - PoE (IEEE 802.3af) compliant, PoE+ (30W) IEEE 802.3at compliant, PoE shutdown feature. UL/cUL Listed (UL60950-1), CE approved. Includes TP2450 Plug-in transformer 24VAC/50VA, 115VAC input.	\$60.58	104.44

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
NETWAY3012	12VDC/30W NetWay midspan adapter for IP cameras and devices, UL/cUL Listed (UL60950-1).	\$55.42	95.56
NETWAY4ESK	4-Port Managed PoE/PoE+ Switch and midspan Injector (Kit) - each port provides PoE (15.4W) or PoE+ (30W) -Total power of 84W Max., PoE shutdown feature. IP management facilitates programming and status monitoring via LAN/WAN.	\$457.56	788.89
NETWAY8	8-Port Midspan - each port provides PoE (IEEE 802.3af) compliant. Total power 150W. 1U EIA 19" Rack Mount Chassis. 115VAC Input. UL/cUL Listed (UL60950-1), UL Listed (UL294).	\$317.71	547.78
NETWAY8M	8-Port Managed Midspan - each port provides PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at) compliant. Total power 150W, PoE shutdown selectable by port. Ethernet port facilitates programming and status monitoring via laptop or LAN. 1U EIA 19" Rack Mount Chassis. 115VAC Input. UL/cUL Listed (UL60950-1), UL Listed (UL294) .	\$343.49	592.22
NETWAYXT	Repeater extends ethernet/data 100m. PoE (IEEE 802.3af) compliant. UL/cUL Listed (UL60950-1).	\$92.16	158.89
NETWAYXTX	Repeater extends ethernet/data 100m. PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at) compliant. UL/cUL Listed (UL60950-1).	\$97.96	168.89
OLS120	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring, 115/230VAC input.	\$90.22	155.56
OLS120D2	Two (2) Output Power Supply/Charger - Output 1- 12VDC or 24VDC @ 3 amp & Output 2-12VDC @ 1 amp, AC & battery monitoring, 115/230VAC input.	\$126.31	217.78
OLS120D2X	Two (2) Output Power Supply/Charger - Output 1- 12VDC or 24VDC @ 3 amp & Output 2-12VDC @ 1 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	\$163.69	282.22
OLS180	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, 115VAC input.	\$109.56	188.89
OLS20	Power Supply/Charger - 12VDC @ 1 amp or 24VDC @ 500 mA, 115VAC input	\$27.39	47.22
OLS200	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, 115VAC input.	\$122.44	211.11
OLS250	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, 115VAC input.	\$160.47	276.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
OLS75	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, 115/230VAC input.	\$70.89	122.22
PACE16PRM	16-Port Long Range Ethernet over CAT5e Receiver. Transmits IP video/data over CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with Pace1PTM transceiver. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	#####	3732.22
PACE1PRD	60W Cat5e Long Range receiver compatible with eBridge200WPM.	\$127.60	220.00
PACE1PRM	Long Range Ethernet over UTP/CAT5e Receiver. Provides IP video/data over single twisted pair (UTP) up to 150m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at) compliant. Requires Pace1PTM. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$127.60	220.00
PACE1PRMT	Long Range Ethernet over UTP/CAT5e Receiver/Transceiver adapter kit. Transmits IP video/data over single twisted pair (UTP) up to 150m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). UL/cUL Listed (UL60950-1). CE Approved.	\$255.20	440.00
PACE1PTM	Long Range Ethernet over UTP/CAT5e Transceiver. Transmits IP video/data over single twisted pair (UTP) up to 150m or CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with Pace receivers. UL/cUL Listed (UL60950-1). CE and C-Tick Approved.	\$127.60	220.00
PACE4PRM	4-Port Long Range Ethernet over CAT5e Receiver. Transmits IP video/data over CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with Pace1PTM transceiver. UL/cUL Listed (UL60950-1). CE Approved.	\$510.72	880.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
PACE8PRM	8-Port Long Range Ethernet over CAT5e Receiver. Transmits IP video/data over CAT5e up to 500m @ 100mbps full duplex and supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). Compatible with Pace1PTM transceiver. 1U EIA 19" Rack Mount Chassis. UL/cUL Listed (UL60950-1). CE Approved.	#####	1866.11
PD16W	16 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into sixteen (16) fused power outputs, UL Recognized.	\$30.93	53.33
PD16WCB	16 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into sixteen (16) PTC power outputs, UL Recognized.	\$30.93	53.33
PD4	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs.	\$18.04	31.11
PD4CB	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) PTC power outputs.	\$18.04	31.11
PD4UL	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs, UL Recognized.	\$18.69	32.22
PD4ULCB	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) PTC power outputs, UL Recognized.	\$18.69	32.22
PD8	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) fused power outputs.	\$20.62	35.56
PD8CB	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) PTC power outputs.	\$20.62	35.56
PD8UL	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) fused power outputs, UL Recognized.	\$21.27	36.67
PD8ULCB	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) PTC power outputs, UL Recognized.	\$21.27	36.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
PM212	Linear Power Supply/Charger - 12VDC @ 1 amp, AC & battery monitoring.	\$23.20	40.00
PM224	Linear Power Supply/Charger - 24VDC @ 750mA, AC & battery monitoring.	\$23.20	40.00
PMK1	Pole Mount Kit for WP1, WP2 and WP3 enclosures. Fits 2"-8" diameter poles.	\$77.34	133.35
PT2724	2 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Two SPDT contacts rated @ 10 amp/115VAC/28VDC, 100 daily/weekly events, 700 weekly block events, 20 holiday exceptions, LCD display, built-in battery charger.	\$103.11	177.78
PT724A	1 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 50 daily/weekly events, 350 weekly block events, 10 holiday exceptions, LCD display, built-in battery charger.	\$68.96	118.89
PT724AE	1 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 50 daily/weekly events, 350 weekly block events, 10 holiday exceptions, LCD display, built-in battery charger, encl. 8.5"H x 7.5"W x 3.5"D.	\$92.80	160.00
R1224DC16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 4.5 amp per bank of 4 outputs, 18 amp total supply current, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL1012), cUL Listed.	\$393.11	677.78
R2416300UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$238.44	411.11
R2416300ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$238.44	411.11
R2416600UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$283.56	488.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
R2416600ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$283.56	488.89
R2416UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$218.79	377.22
R2416ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$218.79	377.22
R2416ULCBI	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 25 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$297.09	512.22
R2416ULI	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 25 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$297.09	512.22
R2432300UL		\$302.89	522.22
R2432300ULCB	32 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$302.89	522.22
R2432600UL	32 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$348.00	600.00
R2432600ULCB	32 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$348.00	600.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
R248UL	8 Output Rack Mount CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$164.66	283.89
R248ULCB	8 Output Rack Mount CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$164.66	283.89
R248ULCBI	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$215.89	372.22
R248ULI	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$215.89	372.22
R615DC1016	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 10 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$251.33	433.33
R615DC1016CB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 10 amp, PTC outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input.	\$251.33	433.33
R615DC416UL	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$225.56	388.89
R615DC416ULCB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$225.56	388.89
R615DC616UL	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 6 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$238.44	411.11

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
R615DC616ULCB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 6 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$238.44	411.11
R615DC8UL	8 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$219.11	377.78
R615DC8ULCB	8 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$219.11	377.78
RAC120	Relay & Base - 120VAC operation, 12mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC, DIN Rail Mount, UL Recognized.	\$14.89	25.67
RAC24	Relay & Base - 24VAC operation, 45mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC, DIN Rail Mount, UL Recognized.	\$14.89	25.67
RB1224	Relay Module - 12VDC or 24VDC operation, 75mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	\$8.38	14.44
RB30	Heavy Duty Load Switching Relay Module - 12VDC or 24VDC operation, 95mA current draw, SPDT contact rated @ 30 amp/120VAC or 28VDC.	\$13.53	23.33
RB5	Relay Module - 6VDC or 12VDC operation, 120mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	\$8.38	14.44
RB524	Relay Module - 24VDC operation, 40mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	\$8.38	14.44
RB610	Break Away Relay 6 Pack - 12VDC or 24VDC operation, 50mA current draw, SPDT contact rated @ 10 amp/120VAC or 28VDC.	\$25.13	43.33
RB7	Ultra Sensitive Relay Cluster - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger inputs, Seven independent isolated SPDT contacts rated @ 1 amp/120VAC or 28VDC.	\$58.00	100.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
RBOC7	Open Collector Module - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger inputs, Seven independent open collector outputs capable of sinking 100mA each.	\$45.11	77.78
RBR1224	Electronic Ratchet/Toggle Relay Module - 12VDC to 24VDC operation, 3VDC to 24VDC Positive or negative sensitive trigger input, 20mA current draw, DPDT contacts rated @ 0.5 amp/120VAC or 2 amp/28VDC.	\$18.30	31.56
RBSN	Relay Module - 12VDC or 24VDC operation, 15mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	\$8.38	14.44
RBSNTTL	Sensitive Relay Module - 12VDC to 24VDC operation, 3VDC to 24VDC isolated positive or negative trigger input, 18mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	\$11.60	20.00
RBST	Relay Module - 6VDC, 12VDC or 24VDC operation, 30mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	\$8.38	14.44
RBTUL	Sensitive Relay Module - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger input, 30mA current draw, SPDT contact rated @ 1 amp/28VDC, Includes Snap Track, UL Listed Burglary (UL749R).	\$14.89	25.67
RBUL	Relay Module - 12VDC or 24VDC operation, 30mA current draw, SPDT contact rated @ 1 amp/28VDC, Includes Snap Track, UL Listed Burglary (UL749R).	\$8.83	15.22
RDC12	DIN Rail Mount UL Recognized Relay & Base - 12VDC operation, 86mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	\$14.89	25.67
RDC24	DIN Rail Mount UL Recognized Relay & Base - 24VDC operation, 43mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	\$14.89	25.67
RDC48	DIN Rail Mount UL Recognized Relay & Base - 48VDC operation, 20mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	\$14.89	25.67
RE2	2U Rack Mount Battery Enclosure, fits up to four (4) 12VDC/7AH batteries with Quick connect terminals.	\$145.93	251.60

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
RESERV1	Video Surveillance UPS - twelve 24VAC true sine wave outputs rated @ 4 amp and four 12VDC regulated outputs rated @ 2 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$215.24	371.10
RESERV1WP	Outdoor Video Surveillance UPS - twelve 24VAC true sine wave outputs rated @ 4 amp and four 12VDC regulated outputs rated @ 2 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$302.89	522.22
RESERV2	Video Surveillance UPS - sixteen 24VAC true sine wave outputs rated @ 4 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$215.24	371.10
RESERV2WP	Outdoor Video Surveillance UPS - sixteen 24VAC true sine wave outputs rated @ 4 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$302.89	522.23
RESERV3	Video Surveillance UPS - sixteen 12VDC regulated outputs rated @ 8 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$215.24	371.10
RESERV3WP	Outdoor Video Surveillance UPS - sixteen 12VDC regulated outputs rated @ 8 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$302.89	522.23
RESERV4WP	Outdoor Video Surveillance UPS - two 24VAC true sine wave outputs rated @ 4 amp and two 12VDC regulated outputs rated @ 1 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input.	\$302.89	522.23

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
SAV182D	18 Output CCTV Power Supply - 12VDC @ 11 amp, PTC outputs, field installable grounded line cord, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	\$154.67	266.68
SAV18D	18 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	\$122.45	211.12
SAV36D	36 Output CCTV Power Supply - 12VDC @ 11 amp, PTC outputs, field installable grounded line cord, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	\$192.04	331.11
SAV4D	4 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	\$52.98	91.35
SAV9D	9 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	\$75.73	130.57
SMP10	Power Supply/Charger - 12VDC or 24VDC @ 10 amp.	\$115.03	198.33
SMP10C12X	Power Supply/Charger - 12VDC @ 10 amp, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$190.76	328.89
SMP10C24X	Power Supply/Charger - 24VDC @ 10 amp, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$193.98	334.44
SMP10PM	Power Supply/Charger - 12VDC or 24VDC @ 10 amp, AC & battery monitoring.	\$134.37	231.67
SMP10PM12P16	16 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$218.47	376.67
SMP10PM12P16CB	16 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$218.47	376.67
SMP10PM12P4	4 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$200.42	345.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
SMP10PM12P4CB	4 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$200.42	345.56
SMP10PM12P8	8 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$203.00	350.00
SMP10PM12P8CB	8 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$203.00	350.00
SMP10PM24P16	16 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$244.24	421.11
SMP10PM24P16CB	16 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$244.24	421.11
SMP10PM24P4	4 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$226.20	390.00
SMP10PM24P4CB	4 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$226.20	390.00
SMP10PM24P8	8 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$228.78	394.44
SMP10PM24P8CB	8 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$228.78	394.44
SMP10PMC12X	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$195.27	336.67
SMP10PMC24X	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	\$213.31	367.78
SMP3	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 2.5 amp.	\$27.92	48.13
SMP312C	Power Supply/Charger - 12VDC @ 2.5 amp power supply, 12VDC/4AH battery & 16.5VAC/40VA plug-in xfmr.	\$64.32	110.90
SMP312CX	Power Supply/Charger - 12VDC @ 2.5 amp power supply, 12VDC/7AH battery & 16.5VAC/40VA plug-in xfmr.	\$67.34	116.11
SMP3CTX	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	\$111.75	192.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
SMP3E	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 2.5 amp, encl. 8.5"H x 7.5"W x 3.5"D.	\$47.25	81.47
SMP3PM	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring.	\$43.31	74.67
SMP3PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	\$127.21	219.33
SMP5	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 4 amp.	\$41.18	71.00
SMP5CTX	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	\$130.70	225.35
SMP5PM	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring.	\$60.90	105.00
SMP5PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	\$135.33	233.33
SMP7	Power Supply/Charger - 12VDC or 24VDC @ 6 amp.	\$78.49	135.33
SMP7CTX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$171.42	295.56
SMP7PM	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring.	\$93.44	161.11
SMP7PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	\$186.89	322.22
SPACER1	5/8" Nylon Spacer. Package of 25.	\$4.83	8.33
ST1	Snap Track for mounting: RB5, RBSN, RBST, RB30, RB524, RB1224, RBSNTTL.	\$1.55	2.67
ST2	Snap Track for mounting: RB7, RBOC7.	\$3.87	6.67
ST3	Snap Track for mounting for: SMP3, SMP5, AL624, 6062, PT724, PT724A.	\$5.16	8.89

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
STRIKEIT1	Dual Panic Device Power Controller - Independently or simultaneously controlled lock outputs for two 24VDC panic hardware devices with high inrush current requirements. Programmable 1 to 30 sec. timed lock release, Two follower relay outputs, Two delayed momentary relay outputs, One 12VDC & One 24VDC aux. power outputs rated @ 1 amp each, Fire Alarm disconnect, built-in battery charger, encl: 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL294), cUL Listed. MEA & CSFM Approved.	\$302.89	522.22
STRIKEIT2	Panic Device Power Controller - Controlled lock output for 24VDC panic hardware device with high inrush current requirements or a mag lock/electric strike. One 24VDC aux. power output rated @ 0.5 amp, built-in battery charger, encl. 8.5"H x 7.5"W x 3.5"D, Accommodates up to 2 - 12VDC/4AH batteries, 115VAC input. UL Listed (UL294), cUL Listed.	\$167.56	288.89
T16100	Transformer - 16.5VAC/100VA (6.25 amp), 115VAC input	\$35.44	61.11
T1656	Transformer - 16VAC/56VA (3.5 amp), 115VAC input.	\$27.07	46.67
T24130D	Transformer - 24VAC/100VA (4 amp), 115VAC/230VAC input.	\$27.71	47.78
T2428100	Transformer - 24VAC/100VA (4 amp) or 28VAC/100VA (3.5 amp), 115VAC input, UL/cUL Recognized.	\$27.71	47.78
T2428100C	Transformer - 24VAC/100VA (4 amp) or 28VAC/100VA (3.5 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	\$63.80	110.00
T2428175	Transformer - 24VAC/175VA (7.25 amp) or 28VAC/175VA (6 amp), 115VAC input, UL/cUL Recognized.	\$37.89	65.33
T2428175C	Transformer - 24VAC/175VA (7.25 amp) or 28VAC/175VA (6 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	\$74.11	127.78
T2428300	Transformer - 24VAC/300VA (12.5 amp) or 28VAC/300VA (10 amp), 115VAC input.	\$101.50	175.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
T2428300E	Transformer - 24VAC/300VA (12.5 amp) or 28VAC/300VA (10 amp), encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	\$139.20	240.00
T28140D	Transformer - 28VAC/175VA (6.25 amp), 115VAC/230VAC input.	\$44.47	76.67
T2856	Transformer - 28VAC/56VA (2 amp), 115VAC input.	\$27.07	46.67
T2856C	Transformer - 28VAC/56VA (2 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	\$63.80	110.00
T2885D	Transformer - 28VAC/100VA (3.5 amp), 115VAC/230VAC input.	\$30.93	53.33
TAPE1	Double Stick Tape Pads. Package of 25.	\$7.09	12.22
TEMPO2	Universal Two Stage Timer - 12 or 24 volt AC or DC operation, SPDT contact rated @ 2 amp/115VAC/28VDC, adjustable timing range 1 sec.-60 seconds timed door release, daily weekly test mode, one shot activation, door prop alarm, EEPROM memory, LCD Display.	\$37.90	65.35
TP1220	Plug-in transformer - 12VAC/20VA, 115VAC input, UL Listed.	\$6.06	10.44
TP1620	Plug-in transformer - 16VAC/20VA, 115VAC input, UL Listed.	\$6.06	10.44
TP1640	Plug-in transformer - 16VAC/40VA, 115VAC input, UL Listed.	\$8.12	14.00
TP1650	Plug-in transformer - 16VAC/50VA, 115VAC input, UL Listed.	\$10.30	17.76
TP2420	Plug-in transformer - 24VAC/20VA, 115VAC input, UL Listed.	\$6.64	11.44
TP2440	Plug-in transformer - 24VAC/40VA, 115VAC input, UL Listed.	\$8.12	14.00
TP2450	Plug-in transformer - 24VAC/50VA, 115VAC input, UL Listed.	\$10.30	17.76
VB1	Power Conversion Module - Converts 12-24VDC input into regulated 24VDC rated @ 0.75 amp, Modular connector/cable assembly. High impact insulated housing.	\$23.97	41.33
VB1T	Power Conversion Module - Converts 12-24VDC input into regulated 24VDC rated @ 0.75 amp output, screw terminals. High impact insulated housing.	\$22.23	38.33
VB6	Power Conversion Module - Converts one (1) 24VAC/VDC input to two (2) 56VDC outputs (30W max.), Modular connector/cable assembly.	\$45.11	77.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
VERTILINE16	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$283.23	488.33
VERTILINE166	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$327.31	564.33
VERTILINE166C	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$327.31	564.33
VERTILINE166CD	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$327.31	564.33
VERTILINE166D	16 Output Rack Mount CCTV Power Supply - 14 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$327.31	564.33
VERTILINE16C	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$283.23	488.33
VERTILINE16CD	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$283.23	488.33
VERTILINE16D	16 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$283.23	488.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
VERTILINE16DI	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 16 amp, isolated PTC Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	\$361.79	623.78
VERTILINE16I	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 16 amp, isolated fused Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	\$361.79	623.78
VERTILINE24	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$303.15	522.67
VERTILINE246	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$350.26	603.89
VERTILINE246C	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$350.26	603.89
VERTILINE246CD	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$350.26	603.89
VERTILINE246D	24 Output Rack Mount CCTV Power Supply - 14 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$350.26	603.89
VERTILINE24C	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$303.15	522.67

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
VERTILINE24CD	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$303.15	522.67
VERTILINE24D	24 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$303.15	522.67
VERTILINE33D	16 Output Rack Mount Power Supply - 12VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$232.00	400.00
VERTILINE33TD	16 Output Rack Mount Power Supply - 12VDC @ 16 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$300.31	517.78
VERTILINE3D	8 Output Rack Mount Power Supply - 12VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$213.31	367.78
VERTILINE563	Rack Mount Power Supply/Charger – two (2) 56VDC outputs rated @ 3 amp each. 1U EIA 19" Rack Mount Chassis, 115VAC input. Use with: eBridge1PCR, eBridge4PCR, eBridge16PCR. CE and C-Tick Approved	\$300.31	517.78
VERTILINE63D	16 Output Rack Mount Power Supply - 24VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$232.00	400.00
VERTILINE63TD	16 Output Rack Mount Power Supply - 24VDC @ 16 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$300.31	517.78
VERTILINE6D	8 Output Rack Mount Power Supply - 24VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	\$213.31	367.78
VERTILINE8	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$221.04	381.11
VERTILINE83	8 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$242.18	417.56

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
VERTILINE83C	8 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$242.18	417.56
VERTILINE83CD	8 Output Rack Mount CCTV Power Supply - 10 mp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$242.18	417.56
VERTILINE83D	8 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$242.18	417.56
VERTILINE8C	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$221.04	381.11
VERTILINE8CD	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	\$221.04	381.11
VERTILINE8D	8 Output Rack Mount CCTV Power Supply - 5 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	\$221.04	381.11
VERTILINE8DI	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 8 amp, isolated PTC Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	\$260.87	449.78
VERTILINE8I	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 8 amp, isolated fused Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	\$260.87	449.78

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
VR1	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 1 amp, Modular connector/cable assembly. High impact insulated housing.	\$23.97	41.33
VR1T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 1 amp, spring terminals. High impact insulated housing.	\$22.23	38.33
VR1TM5	Power Conversion Module - Converts 24VAC or 24VDC input into 5VDC rated @ 1 amp, spring terminals. High impact insulated housing.	\$22.23	38.33
VR2T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 0.5 amp spring terminals. High impact insulated housing.	\$17.21	29.67
VR3T	Power Conversion Module - Converts 24VDC input into 12VDC rated @ 2 amp, screw terminals. High impact insulated housing.	\$32.87	56.67
VR4T	Power Conversion Module - Converts 24VDC input into 12VDC rated @ 3 amp output, screw terminals. High impact insulated housing.	\$37.83	65.22
VR5BT	Power Conversion Module/Battery Charger - Converts 24VAC or 24VDC input into 12VDC rated @ 3 amp, spring terminals. High impact insulated housing.	\$42.99	74.12
VR5T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 3 amp, spring terminals. High impact insulated housing.	\$41.05	70.78
WAYPOINT10A	1 Output Outdoor CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$134.04	231.10
WAYPOINT17A	1 Output Outdoor CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$141.78	244.45
WAYPOINT17A4U	4 Output Outdoor CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, Fused outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input. UL Listed (UL60950-1, UL 60950-22).	\$156.60	270.00

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
WAYPOINT17A4DU	4 Output Outdoor CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, PTC outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$156.60	270.00
WAYPOINT3	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 2.5 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$160.79	277.22
WAYPOINT307A	2 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 277VAC input.	\$244.88	422.20
WAYPOINT30A	2 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$219.11	377.78
WAYPOINT30A4U	4 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, Fused outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input. UL Listed (UL60950-1, UL 60950-22). CE Approved.	\$228.13	393.33
WAYPOINT30A4DU	4 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input. UL Listed (UL60950-1, UL 60950-22). CE Approved.	\$228.13	393.33
WAYPOINT30A8U	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, Fused outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input. UL Listed (UL60950-1, UL 60950-22). CE Approved.	\$232.00	400.00
WAYPOINT30A8DU	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC outputs, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input. UL Listed (UL60950-1, UL 60950-22). CE Approved.	\$232.00	400.00
WAYPOINT5	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 4 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	\$186.89	322.22

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
WAYPOINT7	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 6 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115VAC input.	\$238.12	410.56
WP1	Enclosure - NEMA 4/IP65 outdoor rated 12"H x 8"W x 6"D.	\$100.54	173.35
WP2	Enclosure - NEMA 4/IP66 outdoor rated 17.5"H x 12"W x 6.625"D.	\$122.44	211.11
WP3	Enclosure - NEMA 4-4X/IP66-11 outdoor rated 13.31"H x 11.31"W x 5.59"D.	\$125.02	215.55
WP4	Enclosure - NEMA 4/4X/IP66-11 outdoor rated 9.5"H x 7.32"W x 4.92"D.	\$122.44	211.11
WPL1	Lock for WP1 Enclosure	\$20.62	35.55
WPL2	Lock for WP2 Enclosure	\$38.67	66.67
WPTV244175UL	4 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, 3 - PTC Class 2 power limited outputs rated @ 2.5 amp & 1 - fused output rated @ 10 amp, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$137.27	236.67
WPTV244300UL	4 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, 3 - PTC Class 2 power limited outputs rated @ 2.5 amp & 1 - fused output rated @ 15 amp, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$157.24	271.11
WPTV248175UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$141.13	243.33
WPTV248175ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$141.13	243.33
WPTV248300UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$170.13	293.33

ALTRONIX MSRP PRICE LIST

MODEL	DESCRIPTION	DIR Price	MSRP
WPTV248300ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$170.13	293.33
WPTV248UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$132.76	228.89
WPTV248ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	\$132.76	228.89

SHIPPING: All shipments are

PAYMENT: Options
 Include Prepayment,
 C.O.D. or Open